ALLPLASTICS

Tel. (02) 9417 6111

Web. www.allplastics.com.au

Fax. (02) 9417 6169 Address. Unit 20/380 Eastern Valley Way, Chatswood, NSW 2067 AUSTRALIA.



SAFETY DATA SHEET

according to 1907/2006 EC, Article 31

Page 1 of 3

Revision

0 Revision date

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name Anti-Static Cleaner

Company Anglo Adhesives & Services Ltd

> Anglo House The Airfield Dalby Road Melton Mowbray

Leicestershire LE13 0BL sales@anglo-adhesives.co.uk www.anglo-adhesives.co.uk

Telephone +44 (0)1664 480866 Fax +44 (0)1664 480963 **Emergency telephone** +44 (0)1664 480866

number

2 HAZARDS IDENTIFICATION.

Main hazards Irritating to eyes and skin.

3. COMPOSITION / INFORMATION ON INGREDIENTS.

Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
Sodium hydroxide	0 - 3%	1310-73-2	215-185-5	C; R35
(N-Benzyl)-N,N,N-tributyl)ammonium 4-dodecylbenzenesulfonate	0 - 3%		422-200-0	C; R34 Xn; R22 N; R51/53
Isopropanol (Propan-2-ol)	1 - 10%	67-63-0	200-661-7	F; R11 Xi; R36 R67

4. FIRST AID MEASURES

Skin contact Irritating to skin. Wash off immediately with plenty of soap and water. Remove

contaminated clothing. Seek medical attention if irritation or symptoms persist.

Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the Eye contact

eyelids open. Seek medical attention if irritation or symptoms persist.

Inhalation Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest

and irritation of the respiratory system. Move the exposed person to fresh air. Seek

medical attention.

Ingestion Ingestion may cause nausea and vomiting. Seek medical attention if irritation or

symptoms persist. DO NOT INDUCE VOMITING.

5. FIRE FIGHTING MEASURES

Carbon oxides. **Extinguishing media**

Fire hazards Burning produces irritating, toxic and obnoxious fumes.

Protective equipment Wear suitable respiratory equipment when necessary.

0

Revision
Revision date

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Ensure adequate ventilation of the working area. Wear suitable protective equipment.

Environmental

Do not allow product to enter drains. Prevent further spillage if safe.

precautions

Clean up methods Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled

containers for disposal. Clean spillage area thoroughly with plenty of water.

7. HANDLING AND STORAGE

Handling Avoid contact with eyes and skin. Ensure adequate ventilation of the working area.

Adopt best Manual Handling considerations when handling, carrying and dispensing.

Storage Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in

correctly labelled containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits

Sodium hydroxide WEL 8-hr limit ppm: - WEL 8-hr limit mg/m3: -

WEL 15 min limit ppm: - WEL 15 min limit mg/m3: 2

Isopropanol WEL 8-hr limit ppm: 400 WEL 8-hr limit mg/m3: 999 (Propan-2-ol) WEL 15 min limit ppm: 500 WEL 15 min limit mg/m3: 1250

Engineering measures Ensure adequate ventilation of the working area.

Respiratory protection Wear: Suitable respiratory equipment.

Hand protection Chemical resistant gloves (PVC)

Eye protection Approved safety goggles.

Protective equipment Wear chemical protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

DescriptionLiquid.ColourBlue.OdourPleasant.Boiling point100°CRelative density1.03

Water solubility soluble in water.

10. STABILITY AND REACTIVITY

Stability Stable under normal conditions.

11. TOXICOLOGICAL INFORMATION

Toxicological Irritating to eyes and skin. **information**

12. ECOLOGICAL INFORMATION

Ecotoxicity No known adverse environmental effects.

13. DISPOSAL CONSIDERATIONS

General information Dispose of in compliance with all local and national regulations.

14. TRANSPORT INFORMATION

Further information The product is not classifed as dangerous for carriage.

0

Revision

Revision date

15. REGULATORY INFORMATION

Labelling The product is classified in accordance with 67/548/EEC.

Symbols Xi - Irritant



Risk phrases R36/38 - Irritating to eyes and skin.

16. OTHER INFORMATION

Text of risk phrases in

R11 - Highly flammable.

Section 3.

R22 - Harmful if swallowed.

R34 - Causes burns.

R35 - Causes severe burns.

R36 - Irritating to eyes.

R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R67 - Vapours may cause drowsiness and dizziness.

Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or

in any other process.