

PLASKOLITE, INC.

POST OFFICE BOX 1497
COLUMBUS, OHIO 43216
614/294-3281
FAX 614/297-7282

January 9, 2009

Re: *Material Flammability Characteristics*
- Plaskolite Acrylic Plastic Sheet

To Whom It May Concern:

Plaskolite, Inc.'s acrylic plastic sheets, including our light-transmitting panels, meet the following flammability requirements:

<i>Requirement</i>	<i>Plaskolite Acrylic Sheet Flammability Characteristic</i>
UL	UL 94HB listed (Report# QMFZ2.E87887)
ICC (formerly ICBO)	CC-2 plastic (Report# ESR-2590 & ESR-2591)
NY State Uniform Fire Prevention & Building Code	Article 15 File# 16020-891121-1001 to 1005
ASTM D-635	< 2.5 inch/min (CC-2 plastic)
ASTM D-1929 *	> 650°F self-ignition temperature
ASTM D-2843 *	< 75 smoke-developed index
ASTM E-84 **	Only 0.118" Optix® acrylic sheet can meet flame spread index < 200 and smoke developed index < 450

* The ASTM D-1929 and ASTM D-2843 requirements are alternate requirements to the ASTM E-84 requirements in many building codes.

** These are requirements for Interior Finishes (Chapter 8) in the International Building Code. Many other codes provide an alternate requirement using ASTM D-1929 and ASTM D-2843.

Please feel free to call us if you have further questions regarding this submittal.

Sincerely,



Timothy W. Ling, P.E.
Environmental Engineer