

Perspex® Brand 10 Year Guarantee Cell Cast Acrylic Sheet Colours

Standard (Signs) Colours

Lucite International guarantees that Perspex® cast acrylic sheet for exterior signs will comply in service with the performance specifications set out by Lucite International in the Appendix hereto for a period of ten years subject to the following conditions:

- The guarantee period of ten years runs from the date of delivery of the sheet to the customer.
- 2. The guarantee covers the quality of the sheet as delivered and in particular:
 - 2.1 The sheet must be appropriately stored and transported prior to fabrication and installation.
 - 2.2 High standards of workmanship shall be used in fabrication and installation and Lucite International will not be liable for any failure attributable to poor standards of such workmanship.
 - 2.3 The guarantee does not cover any failure attributable to causes not usually associated with the normal use of Perspex® acrylic sheet and in particular does not apply to harm caused by chemical agents, cleaning fluids, unsuitable sealants or decorative materials.
- Lucite International must be given immediate notice
 of any complaint. Sufficient evidence of the
 complaint must be given to Lucite International and
 those authorised by it must be allowed adequate
 facilities to substantiate any complaint.
- 4. If any Perspex® acrylic sheet shall be shown to Lucite International's satisfaction to have failed to comply with the said performance specifications within the stipulated time limit Lucite International shall replace the failed sheet with an equivalent amount of Perspex® acrylic sheet or other suitable alternative sheet to be delivered free of charge by Lucite International to a delivery point to be nominated by the customer, but Lucite International shall under no circumstances be responsible for any other damage or loss howsoever arising whether directly or indirectly.
- 5. Lucite International gives no guarantee or warranty express or implied in relation to Perspex acrylic sheet apart from the guarantee given herein.
- This guarantee and all the terms thereof shall apply to all deliveries of Perspex[®] supplied by Lucite International until the guarantee is revoked by either of the parties.

Revocation may be effected by either party serving on the other notice in writing to that effect at any time. Revocation shall not affect deliveries of sheet made prior to the date of revocation which shall continue to be fully covered by the terms of this guarantee.

- 7. If the customer shall bring any claim under this guarantee it shall produce documentary evidence to Lucite International's satisfaction that the sheet in question is Perspex® made by Lucite International.
- This guarantee document relates to signs exposed in Australia fabricated from Perspex[®] acrylic sheet.

Appendix

Outdoor ageing behaviour of Perspex[®] cast acrylic sheet for sign applications:

1. Elastic Modulus

The rigidity of Perspex® acrylic will remain substantially unchanged in service. This means that the elastic modulus of a sample cut from a section of Perspex® acrylic sheet will not be less than 2500 MPa as delivered and for ten years after delivery (test method: ISO 178 measured on specimens removed from the exposed Perspex® acrylic installation).

2. Tensile Strength

Perspex[®] will suffer no unacceptable change in brittleness. This means that the tensile strength as delivered and for ten years after delivery of a sample cut from a section of Perspex[®] will not be less than 50 MPa. (test method: ISO R 527 measured on specimens, removed from the exposed Perspex[®]).

3. Colourfastness

During a ten year outdoor exposure period all coloured surfaces can be expected to exhibit at least some degree of change. Lucite International guarantees that any changes in colour of the Perspex[®] sheet will be so small as to pass undetected by the casual observer at street level to the exposed Perspex[®] acrylic.

LUCITE INTERNATIONAL 2016

Perspex[®] and Lucite[®] are registered Trade Marks owned by Lucite International UK Limited.



Tel. (02) 8038 2000 Fax. (02) 9417 6169 Website. www.allplastics.com.au Address. Unit 20/ 380 Eastern Valley Way, Chatswood, NSW 2067 Australia.